

3747
84

Attorney Docket: 381NT/48610CO
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: KENJI NAKABAYASHI ET AL
Serial No.: 10/024,246 Group Art Unit: 3747
Filed: DECEMBER 21, 2001 Examiner: (Not yet assigned)
Title: IGNITION COIL FOR INTERNAL COMBUSTION ENGINE

ADDITIONAL CLAIMS FEE TRANSMITTAL

Commissioner for Patents
Washington, D.C. 20231

Sir:

Transmitted herewith is an Amendment for filing and the filing fee is calculated below:

For	No. After Amendment	Highest No. Prev. Filed	No. Extra	Rate	Fee
Total Claims	19	- 20	= 0	x \$ 9/\$18	= \$
Indep. Claims	16	- 6	= 10	x \$42/\$84	= \$840.00
TOTAL:					\$840.00

☒ A check in the amount of \$840.00 is enclosed.

☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Account No. 05-1323 (Docket #381NT/48610CO). A duplicate copy of this sheet is attached.

Respectfully submitted,

April 5, 2002


James F. McKeown
Registration No. 25,406

CROWELL & MORING, LLP
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844

JFM/acd
56208.043

RECEIVED
APR - 9 2002
TECHNOLOGY CENTER 3700



#5/c
4/15/02
JP

Attorney Docket: 381NT/48610CO
PATENT



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: KENJI NAKABAYASHI ET AL

Serial No.: 10/024,246

Group Art Unit: 3747

Filed: DECEMBER 21, 2001

Examiner: (Not yet assigned)

Title: IGNITION COIL FOR INTERNAL COMBUSTION ENGINE

SECOND PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Sir:

Please enter the following amendments to the claims prior to the examination of the application.

IN THE CLAIMS:

Cancel Claims 1-13.

Please add the following new claims:

RECEIVED

APR 09 2002

TECHNOLOGY CENTER R3700

sub E3
14. (New) An independent ignition type ignition coil for an internal combustion engine which is used after being inserted into a plug hole in the internal combustion engine and being directly coupled to a corresponding ignition plug and of which portion being inserted into the plug hole has an outer diameter of 18mm~27mm, and which includes a center core, a secondary coil wound around a secondary coil bobbin and a primary coil wound around a primary coil bobbin arranged concentrically in a coil casing in this order from the

04/08/2002 HTECKLUI 00000092 10024246

01 FC:102

840.00 DP